

1 INTERNET-DRAFT
2 <draft-ietf-ipp-protocol-v11-04.txt>

Robert Herriot (editor)
Xerox Corporation
Sylvan Butler
Hewlett-Packard
Paul Moore
Peerless Systems Networking
Randy Turner
2wire.com
John Wenn
Xerox Corporation
February 23, 2000

14 Internet Printing Protocol/1.1: Encoding and Transport
15 Copyright (C)The Internet Society (2000). All Rights Reserved.

16
17
18 Status of this Memo

19 This document is an Internet-Draft and is in full conformance with all provisions of Section 10 of [RFC2026]. Internet-Drafts are
20 working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may
21 also distribute working documents as Internet-Drafts.

22 Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other
23 documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in
24 progress".

25 The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>

26 The list of Internet-Draft Shadow Directories can be accessed as <http://www.ietf.org/shadow.html>.

27 Abstract

28 This document is one of a set of documents, which together describe all aspects of a new Internet Printing Protocol (IPP). IPP is
29 an application level protocol that can be used for distributed printing using Internet tools and technologies. This document
30 defines the rules for encoding IPP operations and IPP attributes into a new Internet mime media type called "application/ipp".
31 This document also defines the rules for transporting over HTTP a message body whose Content-Type is "application/ipp". This
32 document defines a new scheme named 'ipp' for identifying IPP printers and jobs.

33 The full set of IPP documents includes:

- 34 Design Goals for an Internet Printing Protocol [RFC2567]
- 35 Rationale for the Structure and Model and Protocol for the Internet Printing Protocol [RFC2568]
- 36 Internet Printing Protocol/1.1: Model and Semantics [ipp-mod]
- 37 Internet Printing Protocol/1.1: Encoding and Transport (this document)
- 38 Internet Printing Protocol/1.1: Implementer's Guide [ipp-iig]
- 39 Mapping between LPD and IPP Protocols [RFC2569]

40 The document, "Design Goals for an Internet Printing Protocol", takes a broad look at distributed printing functionality, and it
41 enumerates real-life scenarios that help to clarify the features that need to be included in a printing protocol for the Internet. It
42 identifies requirements for three types of users: end users, operators, and administrators. It calls out a subset of end user
43 requirements that are satisfied in IPP/1.1. A few OPTIONAL operator operations have been added to IPP/1.1.

44 The document, "Rationale for the Structure and Model and Protocol for the Internet Printing Protocol", describes IPP from a high
45 level view, defines a roadmap for the various documents that form the suite of IPP specification documents, and gives
46 background and rationale for the IETF working group's major decisions.

47 The document, "Internet Printing Protocol/1.1: Model and Semantics", describes a simplified model with abstract objects, their
48 attributes, and their operations that are independent of encoding and transport. It introduces a Printer and a Job object. The Job
49 object optionally supports multiple documents per Job. It also addresses security, internationalization, and directory issues.

50 The document "Internet Printing Protocol/1.1: Implementer's Guide", gives advice to implementers of IPP clients and IPP
51 objects.

52 The document "Mapping between LPD and IPP Protocols" gives some advice to implementers of gateways between IPP and
53 LPD (Line Printer Daemon) implementations.

54 Table of Contents

55	1.	Introduction.....	3
56	2.	Conformance Terminology	4
57	3.	Encoding of the Operation Layer	4
58	3.1	Picture of the Encoding	4
59	3.2	Syntax of Encoding	7
60	3.3	Version-number	8
61	3.4	Operation-id.....	8
62	3.5	Status-code	8
63	3.6	Request-id.....	8
64	3.7	Tags	8
65	3.7.1	Delimiter Tags	8
66	3.7.2	Value Tags	9
67	3.8	Name-Length.....	11
68	3.9	(Attribute) Name	11
69	3.10	Value Length	12
70	3.11	(Attribute) Value	12
71	3.12	Data	13
72	4.	Encoding of Transport Layer	14
73	5.	IPP URL Scheme	14
74	6.	IANA Considerations.....	15
75	7.	Internationalization Considerations.....	16
76	8.	Security Considerations.....	16
77	8.1	Security Conformance Requirements	16
78	8.1.1	Digest Authentication.....	16
79	8.1.2	Transport Layer Security (TLS).....	17
80	8.2	Using IPP with TLS.....	17
81	9.	Interoperability with IPP/1.0 Implementations	17
82	9.1	The "version-number" Parameter	18
83	9.2	Security and URL Schemes	18
84	10.	References.....	18
85	11.	Author's Address.....	20
86	12.	Other Participants:	21
87	13.	Appendix A: Protocol Examples.....	22
88	13.1	Print-Job Request	22
89	13.2	Print-Job Response (successful)	23
90	13.3	Print-Job Response (failure)	24
91	13.4	Print-Job Response (success with attributes ignored).....	25
92	13.5	Print-URI Request	27
93	13.6	Create-Job Request.....	27
94	13.7	Get-Jobs Request.....	28
95	13.8	Get-Jobs Response.....	29
96	14.	Appendix B: Registration of MIME Media Type Information for "application/ipp".....	31
97	15.	Appendix C: Changes from IPP/1.0.....	32
98	16.	Full Copyright Statement	33

99 **1. Introduction**

100 This document contains the rules for encoding IPP operations and describes two layers: the transport layer and the operation
101 layer.

102 The transport layer consists of an HTTP/1.1 request or response. RFC 2616 [RFC2616] describes HTTP/1.1. This document
103 specifies the HTTP headers that an IPP implementation supports.

104 The operation layer consists of a message body in an HTTP request or response. The document "Internet Printing Protocol/1.1:
105 Model and Semantics" [ipp-mod] defines the semantics of such a message body and the supported values. This document
106 specifies the encoding of an IPP operation. The aforementioned document [ipp-mod] is henceforth referred to as the "IPP model
107 document"

108 **2. Conformance Terminology**

109 The key words "MUST", "MUST NOT", "REQUIRED", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and
110 "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [RFC2119].

111 **3. Encoding of the Operation Layer**

112 The operation layer MUST contain a single operation request or operation response. Each request or response consists of a
113 sequence of values and attribute groups. Attribute groups consist of a sequence of attributes each of which is a name and value.
114 Names and values are ultimately sequences of octets

115 The encoding consists of octets as the most primitive type. There are several types built from octets, but three important types are
116 integers, character strings and octet strings, on which most other data types are built. Every character string in this encoding
117 MUST be a sequence of characters where the characters are associated with some charset and some natural language. A character
118 string MUST be in "reading order" with the first character in the value (according to reading order) being the first character in
119 the encoding. A character string whose associated charset is US-ASCII whose associated natural language is US English is
120 henceforth called a US-ASCII-STRING. A character string whose associated charset and natural language are specified in a
121 request or response as described in the model document is henceforth called a LOCALIZED-STRING. An octet string MUST be
122 in "IPP model document order" with the first octet in the value (according to the IPP model document order) being the first octet
123 in the encoding. Every integer in this encoding MUST be encoded as a signed integer using two's-complement binary encoding
124 with big-endian format (also known as "network order" and "most significant byte first"). The number of octets for an integer
125 MUST be 1, 2 or 4, depending on usage in the protocol. Such one-octet integers, henceforth called SIGNED-BYTE, are used for
126 the version-number and tag fields. Such two-byte integers, henceforth called SIGNED-SHORT are used for the operation-id,
127 status-code and length fields. Four byte integers, henceforth called SIGNED-INTEGER, are used for values fields and the
128 sequence number.

129 The following two sections present the operation layer in two ways

- 130 - informally through pictures and description
- 131 - formally through Augmented Backus-Naur Form (ABNF), as specified by RFC 2234 [RFC2234]

132

133 **3.1 Picture of the Encoding**

134 The encoding for an operation request or response consists of:

135	-----		
136		version-number	2 bytes - required
137	-----		
138		operation-id (request)	2 bytes - required
139		or	
140		status-code (response)	
141	-----		
142		request-id	4 bytes - required
143	-----		
144		xxx-attributes-tag	1 byte -0 or more
145	-----		
146		xxx-attribute-sequence	n bytes
147	-----		
148		end-of-attributes-tag	1 byte - required
149	-----		
150		data	q bytes - optional
151	-----		

152 The xxx-attributes-tag and xxx-attribute-sequence represents four different values of "xxx", namely, operation, job, printer and
 153 unsupported. The xxx-attributes-tag and an xxx-attribute-sequence represent attribute groups in the model document. The xxx-
 154 attributes-tag identifies the attribute group and the xxx-attribute-sequence contains the attributes.

155 The expected sequence of xxx-attributes-tag and xxx-attribute-sequence is specified in the IPP model document for each
 156 operation request and operation response.

157 A request or response SHOULD contain each xxx-attributes-tag defined for that request or response even if there are no attributes
 158 except for the unsupported-attributes-tag which SHOULD be present only if the unsupported-attribute-sequence is non-empty. A
 159 receiver of a request MUST be able to process as equivalent empty attribute groups:

- 160 a) an xxx-attributes-tag with an empty xxx-attribute-sequence,
- 161 b) an expected but missing xxx-attributes-tag.

162 The data is omitted from some operations, but the end-of-attributes-tag is present even when the data is omitted. Note, the xxx-
 163 attributes-tags and end-of-attributes-tag are called 'delimiter-tags'. Note: the xxx-attribute-sequence, shown above may consist of
 164 0 bytes, according to the rule below.

165 An xxx-attributes-sequence consists of zero or more compound-attributes.

166	-----		
167		compound-attribute	s bytes - 0 or more
168	-----		

169 A compound-attribute consists of an attribute with a single value followed by zero or more additional values.

170 Note: a 'compound-attribute' represents a single attribute in the model document. The 'additional value' syntax is for attributes
 171 with 2 or more values.

172 Each attribute consists of:

173	-----		
174		value-tag	1 byte
175	-----		
176		name-length (value is u)	2 bytes
177	-----		
178		name	u bytes
179	-----		
180		value-length (value is v)	2 bytes
181	-----		
182		value	v bytes
183	-----		

184 An additional value consists of:

185	-----		
186		value-tag	1 byte
187	-----		
188		name-length (value is 0x0000)	2 bytes
189	-----		
190		value-length (value is w)	2 bytes
191	-----		
192		value	w bytes
193	-----		

-0 or more

194
195 Note: an additional value is like an attribute whose name-length is 0.

196 From the standpoint of a parsing loop, the encoding consists of:

197	-----		
198		version-number	2 bytes - required
199	-----		
200		operation-id (request)	2 bytes - required
201		or	
202		status-code (response)	
203	-----		
204		request-id	4 bytes - required
205	-----		
206		tag (delimiter-tag or value-tag)	1 byte
207	-----		
208		empty or rest of attribute	x bytes
209	-----		
210		end-of-attributes-tag	2 bytes - required
211	-----		
212		data	y bytes - optional
213	-----		
214			

-0 or more

215 The value of the tag determines whether the bytes following the tag are:

- 216 - attributes
- 217 - data
- 218 - the remainder of a single attribute where the tag specifies the type of the value.

219 **3.2 Syntax of Encoding**

220 The syntax below is ABNF [RFC2234] except 'strings of literals' MUST be case sensitive. For example 'a' means lower case 'a'
 221 and not upper case 'A'. In addition, SIGNED-BYTE and SIGNED-SHORT fields are represented as '%x' values which show
 222 their range of values.

```

223 ipp-message = ipp-request / ipp-response
224 ipp-request = version-number operation-id request-id
225             *(xxx-attributes-tag xxx-attribute-sequence) end-of-attributes-tag data
226 ipp-response = version-number status-code request-id
227             *(xxx-attributes-tag xxx-attribute-sequence) end-of-attributes-tag data
228 xxx-attribute-sequence = *compound-attribute
229
230 xxx-attributes-tag = operation-attributes-tag / job-attributes-tag /
231                   printer-attributes-tag / unsupported-attributes-tag
232
233 version-number = major-version-number minor-version-number
234 major-version-number = SIGNED-BYTE ; initially %d1
235 minor-version-number = SIGNED-BYTE ; initially %d0
236
237 operation-id = SIGNED-SHORT ; mapping from model defined below
238 status-code = SIGNED-SHORT ; mapping from model defined below
239 request-id = SIGNED-INTEGER ; whose value is > 0
240
241 compound-attribute = attribute *additional-values
242
243 attribute = value-tag name-length name value-length value
244 additional-values = value-tag zero-name-length value-length value
245
246 name-length = SIGNED-SHORT ; number of octets of 'name'
247 name = LALPHA *( LALPHA / DIGIT / "-" / "_" / "." )
248 value-length = SIGNED-SHORT ; number of octets of 'value'
249 value = OCTET-STRING
250
251 data = OCTET-STRING
252
253 zero-name-length = %x00.00 ; name-length of 0
254 operation-attributes-tag = %x01 ; tag of 1
255 job-attributes-tag = %x02 ; tag of 2
256 printer-attributes-tag = %x04 ; tag of 4
257 unsupported- attributes-tag = %x05 ; tag of 5
258 end-of-attributes-tag = %x03 ; tag of 3
259 value-tag = %x10-FF
260
261 SIGNED-BYTE = BYTE
262 SIGNED-SHORT = 2BYTE
263 SIGNED-INTEGER = 4BYTE
264 DIGIT = %x30-39 ; "0" to "9"
265 LALPHA = %x61-7A ; "a" to "z"
266 BYTE = %x00-FF
267 OCTET-STRING = *BYTE
268

```

269 The syntax allows an xxx-attributes-tag to be present when the xxx-attribute-sequence that follows is empty. The syntax is
 270 defined this way to allow for the response of Get-Jobs where no attributes are returned for some job-objects. Although it is

271 RECOMMENDED that the sender not send an xxx-attributes-tag if there are no attributes (except in the Get-Jobs response just
272 mentioned), the receiver MUST be able to decode such syntax.

273 3.3 Version-number

274 The version-number MUST consist of a major and minor version-number, each of which MUST be represented by a SIGNED-
275 BYTE. The protocol described in this document MUST have a major version-number of 1 (0x01) and a minor version-number of
276 1 (0x01). The ABNF for these two bytes MUST be %x01.01.

277 3.4 Operation-id

278 Operation-ids are defined as enums in the model document. An operation-ids enum value MUST be encoded as a SIGNED-
279 SHORT.

280 3.5 Status-code

281 Status-codes are defined as enums in the model document. A status-code enum value MUST be encoded as a SIGNED-SHORT.

282 The status-code is an operation attribute in the model document. In the protocol, the status-code is in a special position, outside of
283 the operation attributes.

284 If an IPP status-code is returned, then the HTTP Status-Code MUST be 200 (successful-ok). With any other HTTP Status-Code
285 value, the HTTP response MUST NOT contain an IPP message-body, and thus no IPP status-code is returned.

286 3.6 Request-id

287 The request-id allows a client to match a response with a request. This mechanism is unnecessary in HTTP, but may be useful
288 when application/ipp entity bodies are used in another context.

289 The request-id in a response MUST be the value of the request-id received in the corresponding request. A client can set the
290 request-id in each request to a unique value or a constant value, such as 1, depending on what the client does with the request-id
291 returned in the response. The value of the request-id MUST be greater than zero.

292 3.7 Tags

293 There are two kinds of tags:

- 294 - delimiter tags: delimit major sections of the protocol, namely attributes and data
- 295 - value tags: specify the type of each attribute value

296 3.7.1 Delimiter Tags

297 The following table specifies the values for the delimiter tags:

Tag Value (Hex)	Delimiter
0x00	reserved for definition in a future IETF standards track document
0x01	operation-attributes-tag
0x02	job-attributes-tag
0x03	end-of-attributes-tag
0x04	printer-attributes-tag
0x05	unsupported-attributes-tag
0x06-0x0e	reserved for future delimiters in IETF standards track documents
0x0F	reserved for future chunking-end-of-attributes-tag for definition in a future IETF standards track document

298 When an xxx-attributes-tag occurs in the protocol, it MUST mean that zero or more following attributes up to the next delimiter
299 tag are attributes belonging to group xxx as defined in the model document, where xxx is operation, job, printer, unsupported.

300 Doing substitution for xxx in the above paragraph, this means the following. When an operation-attributes-tag occurs in the
301 protocol, it MUST mean that the zero or more following attributes up to the next delimiter tag are operation attributes as defined
302 in the model document. When an job-attributes-tag occurs in the protocol, it MUST mean that the zero or more following
303 attributes up to the next delimiter tag are job attributes or job template attributes as defined in the model document. When a
304 printer-attributes-tag occurs in the protocol, it MUST mean that the zero or more following attributes up to the next delimiter tag
305 are printer attributes as defined in the model document. When an unsupported-attributes-tag occurs in the protocol, it MUST
306 mean that the zero or more following attributes up to the next delimiter tag are unsupported attributes as defined in the model
307 document.

308 The operation-attributes-tag and end-of-attributes-tag MUST each occur exactly once in an operation. The operation-attributes-
309 tag MUST be the first tag delimiter, and the end-of-attributes-tag MUST be the last tag delimiter. If the operation has a
310 document-content group, the document data in that group MUST follow the end-of-attributes-tag.

311 Each of the other three xxx-attributes-tags defined above is OPTIONAL in an operation and each MUST occur at most once in
312 an operation, except for job-attributes-tag in a Get-Jobs response which may occur zero or more times.

313 The order and presence of delimiter tags for each operation request and each operation response MUST be that defined in the
314 model document. For further details, see section 3.9 "Operation Requests and Responses" and 13 "Appendix A: Protocol
315 Examples".

316 A Printer MUST treat the reserved delimiter tags differently from reserved value tags so that the Printer knows that there is an
317 entire attribute group that it doesn't understand as opposed to a single value that it doesn't understand.

318 3.7.2 Value Tags

319 The remaining tables show values for the value-tag, which is the first octet of an attribute. The value-tag specifies the type of the
320 value of the attribute. The following table specifies the "out-of-band" values for the value-tag.

Tag Value (Hex)	Meaning
0x10	unsupported
0x11	reserved for 'default' for definition in a future IETF standards track document
0x12	unknown
0x13	no-value
0x14-0x1F	reserved for "out-of-band" values in future IETF standards track documents.

321 The "unsupported" value MUST be used in the attribute-sequence of an error response for those attributes which the printer does
322 not support. The "default" value is reserved for future use of setting value back to their default value. The "unknown" value is

323 used for the value of a supported attribute when its value is temporarily unknown. The "no-value" value is used for a supported
 324 attribute to which no value has been assigned, e.g. "job-k-octets-supported" has no value if an implementation supports this
 325 attribute, but an administrator has not configured the printer to have a limit.

326 The following table specifies the integer values for the value-tag:

Tag Value (Hex)	Meaning
0x20	reserved for definition in a future IETF standards track document
0x21	integer
0x22	boolean
0x23	enum
0x24-0x2F	reserved for integer types for definition in future IETF standards track documents

327 NOTE: 0x20 is reserved for "generic integer" if it should ever be needed.

328 The following table specifies the octetString values for the value-tag:

Tag Value (Hex)	Meaning
0x30	octetString with an unspecified format
0x31	dateTime
0x32	resolution
0x33	rangeOfInteger
0x34	reserved for definition in a future IETF standards track document
0x35	textWithLanguage
0x36	nameWithLanguage
0x37-0x3F	reserved for octetString type definitions in future IETF standards track documents

329 The following table specifies the character-string values for the value-tag:

Tag Value (Hex)	Meaning
0x40	reserved for definition in a future IETF standards track document
0x41	textWithoutLanguage
0x42	nameWithoutLanguage
0x43	reserved for definition in a future IETF standards track document
0x44	keyword
0x45	uri
0x46	uriScheme
0x47	charset
0x48	naturalLanguage
0x49	mimeMediaType
0x4A-0x5F	reserved for character string type definitions in future IETF standards track documents

330 NOTE: 0x40 is reserved for "generic character-string" if it should ever be needed.

331 NOTE: an attribute value always has a type, which is explicitly specified by its tag; one such tag value is
 332 "nameWithoutLanguage". An attribute's name has an implicit type, which is keyword.

333 The values 0x60-0xFF are reserved for future definitions in IETF standards track documents.

334 The tag 0x7F is reserved for extending types beyond the 255 values available with a single byte. A tag value of 0x7F MUST
335 signify that the first 4 bytes of the value field are interpreted as the tag value. Note, this future extension doesn't affect parsers
336 that are unaware of this special tag. The tag is like any other unknown tag, and the value length specifies the length of a value
337 which contains a value that the parser treats atomically. Values from 0x00 to 0x37777777 are reserved for definition in future
338 IETF standard track documents. The values 0x40000000 to 0x7FFFFFFF are reserved for vendor extensions.

339 3.8 Name-Length

340 The name-length field MUST consist of a SIGNED-SHORT. This field MUST specify the number of octets in the name field
341 which follows the name-length field, excluding the two bytes of the name-length field.

342 If a name-length field has a value of zero, the following name field MUST be empty, and the following value MUST be treated as
343 an additional value for the preceding attribute. Within an attribute-sequence, if two or more attributes have the same name, the
344 attribute-sequence is mal-formed (see [ipp-mod] section 3.1.3). The zero-length name is the only mechanism for multi-valued
345 attributes.

346 3.9 Operation Requests and Responses

347 Some operation elements are called parameters in the model document [ipp-mod]. They MUST be encoded in a special position
348 and they MUST NOT appear as an operation attributes. These parameters are:

- 349 - "version-number": The parameter named "version-number" in the IPP model document MUST become the "version-
350 number" field in the operation layer request or response.
- 351 - "operation-id": The parameter named "operation-id" in the IPP model document MUST become the "operation-id" field
352 in the operation layer request.
- 353 - "status-code": The parameter named "status-code" in the IPP model document MUST become the "status-code" field in
354 the operation layer response.
- 355 - "request-id": The parameter named "request-id" in the IPP model document MUST become the "request-id" field in the
356 operation layer request or response.
357

358 All Printer and Job objects are identified by a Uniform Resource Identifier (URI) [RFC2396] so that they can be persistently and
359 unambiguously referenced. The notion of a URI is a useful concept, however, until the notion of URI is more stable (i.e.,
360 defined more completely and deployed more widely), it is expected that the URIs used for IPP objects will actually be URLs
361 [RFC1738] [RFC1808]. Since every URL is a specialized form of a URI, even though the more generic term URI is used
362 throughout the rest of this document, its usage is intended to cover the more specific notion of URL as well.

363 Some operation elements are encoded twice, once as the request-URI on the HTTP Request-Line and a second time as a
364 REQUIRED operation attribute in the application/ipp entity. These attributes are the target URI for the operation and are called
365 printer-uri and job-uri. Note: The target URI is included twice in an operation referencing the same IPP object, but the two URIs
366 NEED NOT be literally identical. One can be a relative URI and the other can be an absolute URI. HTTP/1.1 allows clients to
367 generate and send a relative URI rather than an absolute URI. A relative URI identifies a resource with the scope of the HTTP
368 server, but does not include scheme, host or port. The following statements characterize how URLs should be used in the
369 mapping of IPP onto HTTP/1.1:

- 370 1. Although potentially redundant, a client MUST supply the target of the operation both as an operation attribute and as a
371 URI at the HTTP layer. The rationale for this decision is to maintain a consistent set of rules for mapping

- 372 application/ipp to possibly many communication layers, even where URLs are not used as the addressing mechanism in
 373 the transport layer.
- 374 2. Even though these two URLs might not be literally identical (one being relative and the other being absolute), they MUST
 375 both reference the same IPP object.
 - 376 3. The URI in the HTTP layer is either relative or absolute and is used by the HTTP server to route the HTTP request to the
 377 correct resource relative to that HTTP server. The HTTP server need not be aware of the URI within the operation
 378 request.
 - 379 4. Once the HTTP server resource begins to process the HTTP request, it might get the reference to the appropriate IPP
 380 Printer object from either the HTTP URI (using to the context of the HTTP server for relative URLs) or from the URI
 381 within the operation request; the choice is up to the implementation.
 - 382 5. HTTP URIs can be relative or absolute, but the target URI in the operation MUST be an absolute URI.

383 The model document arranges the remaining attributes into groups for each operation request and response. Each such group
 384 MUST be represented in the protocol by an xxx-attribute-sequence preceded by the appropriate xxx-attributes-tag (See the table
 385 below and section 13 "Appendix A: Protocol Examples"). In addition, the order of these xxx-attributes-tags and xxx-attribute-
 386 sequences in the protocol MUST be the same as in the model document, but the order of attributes within each xxx-attribute-
 387 sequence MUST be unspecified. The table below maps the model document group name to xxx-attributes-sequence:

Model Document Group	xxx-attributes-sequence
Operation Attributes	operations-attributes-sequence
Job Template Attributes	job-attributes-sequence
Job Object Attributes	job-attributes-sequence
Unsupported Attributes	unsupported- attributes-sequence
Requested Attributes (Get-Job-Attributes)	job-attributes-sequence
Requested Attributes (Get-Printer-Attributes)	printer-attributes-sequence
Document Content	in a special position as described above

388 If an operation contains attributes from more than one job object (e.g. Get-Jobs response), the attributes from each job object
 389 MUST be in a separate job-attribute-sequence, such that the attributes from the ith job object are in the ith job-attribute-sequence.
 390 See Section 13 "Appendix A: Protocol Examples" for table showing the application of the rules above.

391 **3.10 Value Length**

392 Each attribute value MUST be preceded by a SIGNED-SHORT, which MUST specify the number of octets in the value which
 393 follows this length, exclusive of the two bytes specifying the length.

394 For any of the types represented by binary signed integers, the sender MUST encode the value in exactly four octets.

395 For any of the types represented by character-strings, the sender MUST encode the value with all the characters of the string and
 396 without any padding characters.

397 If a value-tag contains an "out-of-band" value, such as "unsupported", the value-length MUST be 0 and the value empty — the
 398 value has no meaning when the value-tag has an "out-of-band" value.

399 **3.11 Attribute Value**

400 The syntax types and most of the details of the representation of attribute values are defined in the IPP model document. The
 401 table below augments the information in the model document, and defines the syntax types from the model document in terms of
 402 the 5 basic types defined in section 3 "Encoding of the Operation Layer". The 5 types are US-ASCII-STRING, LOCALIZED-
 403 STRING, SIGNED-INTEGER, SIGNED-SHORT, SIGNED-BYTE, and OCTET-STRING.

Syntax of Attribute Value**Encoding**

textWithoutLanguage,
nameWithoutLanguage

LOCALIZED-STRING.

textWithLanguage

OCTET_STRING consisting of 4 fields:

- a) a SIGNED-SHORT which is the number of octets in the following field
- b) a value of type natural-language,
- c) a SIGNED-SHORT which is the number of octets in the following field,
- d) a value of type textWithoutLanguage.

The length of a textWithLanguage value MUST be 4 + the value of field a + the value of field c.

nameWithLanguage

OCTET_STRING consisting of 4 fields:

- a) a SIGNED-SHORT which is the number of octets in the following field
- b) a value of type natural-language,
- c) a SIGNED-SHORT which is the number of octets in the following field
- d) a value of type nameWithoutLanguage.

The length of a nameWithLanguage value MUST be 4 + the value of field a + the value of field c.

charset, naturalLanguage,
mimeMediaType, keyword, uri, and
uriScheme

US-ASCII-STRING.

boolean

SIGNED-BYTE where 0x00 is 'false' and 0x01 is 'true'.

integer and enum

a SIGNED-INTEGER.

dateTime

OCTET-STRING consisting of eleven octets whose contents are defined by "DateAndTime" in RFC 1903 [RFC1903].

resolution

OCTET_STRING consisting of nine octets of 2 SIGNED-INTEGERS followed by a SIGNED-BYTE. The first SIGNED-INTEGER contains the value of cross feed direction resolution. The second SIGNED-INTEGER contains the value of feed direction resolution. The SIGNED-BYTE contains the units value.

rangeOfInteger

Eight octets consisting of 2 SIGNED-INTEGERS. The first SIGNED-INTEGER contains the lower bound and the second SIGNED-INTEGER contains the upper bound.

1setOf X

Encoding according to the rules for an attribute with more than 1 value. Each value X is encoded according to the rules for encoding its type.

octetString

OCTET-STRING

404 The type of the value in the model document determines the encoding in the value and the value of the value-tag.

405 **3.12 Data**

406 The data part MUST include any data required by the operation

407 **4. Encoding of Transport Layer**

408 HTTP/1.1 [RFC2616] is the transport layer for this protocol.

409 The operation layer has been designed with the assumption that the transport layer contains the following information:

- 410 - the URI of the target job or printer operation
- 411 - the total length of the data in the operation layer, either as a single length or as a sequence of chunks each with a length.
- 412

413 It is REQUIRED that a printer implementation support HTTP over the IANA assigned Well Known Port 631 (the IPP default
414 port), though a printer implementation may support HTTP over some other port as well.

415 Each HTTP operation MUST use the POST method where the request-URI is the object target of the operation, and where the
416 "Content-Type" of the message-body in each request and response MUST be "application/ipp". The message-body MUST
417 contain the operation layer and MUST have the syntax described in section 3.2 "Syntax of Encoding". A client implementation
418 MUST adhere to the rules for a client described for HTTP1.1 [RFC2616]. A printer (server) implementation MUST adhere the
419 rules for an origin server described for HTTP1.1 [RFC2616].

420 An IPP server sends a response for each request that it receives. If an IPP server detects an error, it MAY send a response before
421 it has read the entire request. If the HTTP layer of the IPP server completes processing the HTTP headers successfully, it MAY
422 send an intermediate response, such as "100 Continue", with no IPP data before sending the IPP response. A client MUST
423 expect such a variety of responses from an IPP server. For further information on HTTP/1.1, consult the HTTP documents
424 [RFC2616].

425 An HTTP server MUST support chunking for IPP requests, and an IPP client MUST support chunking for IPP responses
426 according to HTTP/1.1[RFC2616]. Note: this rule causes a conflict with non-compliant implementations of HTTP/1.1 that
427 don't support chunking for POST methods, and this rule may cause a conflict with non-compliant implementations of HTTP/1.1
428 that don't support chunking for CGI scripts

429 **5. IPP URL Scheme**

430 The IPP/1.1 document defines a new scheme 'ipp' as the value of a URL that identifies either an IPP printer object or an IPP job
431 object. The IPP attributes using the 'ipp' scheme are specified below. Because the HTTP layer does not support the 'ipp' scheme,
432 a client MUST map 'ipp' URLs to 'http' URLs, and then follows the HTTP [RFC2616][RFC2617] rules for constructing a
433 Request-Line and HTTP headers. The mapping is simple because the 'ipp' scheme implies all of the same protocol semantics as
434 that of the 'http' scheme [RFC2616], except that it represents a print service and the implicit (default) port number that clients use
435 to connect to a server is port 631.

436 In the remainder of this section the term 'ipp-URL' means a URL whose scheme is 'ipp' and whose implicit (default) port is 631.
437 The term 'http-URL' means a URL whose scheme is 'http', and the term 'https-URL' means a URL whose scheme is 'https',

438 A client and an IPP object (i.e. the server) MUST support the ipp-URL value in the following IPP attributes.

439 job attributes:

440 job-uri

441 job-printer-uri

442 printer attributes:

443 printer-uri-supported

444 operation attributes:

445 job-uri

446 printer-uri

447

448 Each of the above attributes identifies a printer or job object. The ipp-URL is intended as the value of the attributes in this list,
449 and for no other attributes. All of these attributes have a syntax type of 'uri', but there are attributes with a syntax type of 'uri' that
450 do not use the 'ipp' scheme, e.g. 'job-more-info'.

451

452 If a printer registers its URL with a directory service, the printer MUST register an ipp-URL.

453 User interfaces are beyond the scope of this document. But if software exposes the ipp-URL values of any of the above five
454 attributes to a human user, it is REQUIRED that the human see the ipp-URL as is.

455

456 When a client sends a request, it MUST convert a target ipp-URL to a target http-URL for the HTTP layer according to the
457 following rules:

458

1. change the 'ipp' scheme to 'http'

459

2. add an explicit port 631 if the URL does not contain an explicit port. Note: port 631 is the IANA assigned Well Known
460 Port for the 'ipp' scheme.

460

461 The client MUST use the target http-URL in both the HTTP Request-Line and HTTP headers, as specified by
462 HTTP[RFC2616][RFC2617]. However, the client MUST use the target ipp-URL for the value of the "printer-uri" or "job-uri"
463 operation attribute within the application/ipp body of the request. The server MUST use the ipp-URL for the value of the
464 "printer-uri", "job-uri" or "printer-uri-supported" attributes within the application/ipp body of the response.

465

466 For example, when an IPP client sends a request directly (i.e. no proxy) to an ipp-URL "ipp://myhost.com/myprinter/myqueue",
467 it opens a TCP connection to port 631 (the ipp implicit port) on the host "myhost.com" and sends the following data:

468

469 POST /myprinter/myqueue HTTP/1.1

470 Host: myhost.com:631

471 Content-type: application/ipp

472 Transfer-Encoding: chunked

473

474 "printer-uri" "ipp://myhost.com/myprinter/myqueue"

475 (encoded in application/ipp message body)

476

477

478 As another example, when an IPP client sends the same request as above via a proxy "myproxy.com", it opens a TCP connection
479 to the proxy port 8080 on the proxy host "myproxy.com" and sends the following data:

480

481 POST http://myhost.com:631/myprinter/myqueue HTTP/1.1

482 Host: myhost.com:631

483 Content-type: application/ipp

484 Transfer-Encoding: chunked

485

486 "printer-uri" "ipp://myhost.com/myprinter/myqueue"

487 (encoded in application/ipp message body)

488

489

490 The proxy then connects to the IPP origin server with headers that are the same as the "no-proxy" example above.

491 6. IANA Considerations

492 This section describes the procedures for allocating encoding for the following IETF standards track extensions and vendor
493 extensions to the IPP/1.1 Encoding and Transport document:

494 1. attribute syntaxes - see [ipp-mod] section 6.3

- 495 2. attribute groups - see [ipp-mod] section 6.5
496 3. out-of-band attribute values - see [ipp-mod] section 6.7
497

498 These extensions follow the "type2" registration procedures defined in [ipp-mod] section 6. Extensions registered for use with
499 IPP/1.1 are OPTIONAL for client and IPP object conformance to the IPP/1.1 Encoding and Transport document.

500 These extension procedures are aligned with the guidelines as set forth by the IESG [IANA-CON]. The [ipp-mod] Section 11
501 describes how to propose new registrations for consideration. IANA will reject registration proposals that leave out required
502 information or do not follow the appropriate format described in [ipp-mod] Section 11. The IPP/1.1 Encoding and Transport
503 document may also be extended by an appropriate RFC that specifies any of the above extensions.

504 **7. Internationalization Considerations**

505 See the section on "Internationalization Considerations" in the document "Internet Printing Protocol/1.1: Model and Semantics"
506 [ipp-mod] for information on internationalization. This document adds no additional issues.

507 **8. Security Considerations**

508 The IPP Model and Semantics document [ipp-mod] discusses high level security requirements (Client Authentication, Server
509 Authentication and Operation Privacy). Client Authentication is the mechanism by which the client proves its identity to the
510 server in a secure manner. Server Authentication is the mechanism by which the server proves its identity to the client in a secure
511 manner. Operation Privacy is defined as a mechanism for protecting operations from eavesdropping.

512 **8.1 Security Conformance Requirements**

513 This section defines the security requirements for IPP clients and IPP objects.

514 **8.1.1 Digest Authentication**

515 IPP clients MUST support:

- 516 Digest Authentication [RFC2617].
517 MD5 and MD5-sess MUST be implemented and supported.
518 The Message Integrity feature NEED NOT be used.

519

520 IPP Printers SHOULD support:

- 521 Digest Authentication [RFC2617].
522 MD5 and MD5-sess MUST be implemented and supported.
523 The Message Integrity feature NEED NOT be used.

524

525 The reasons that IPP Printers SHOULD (rather than MUST) support Digest Authentication are:

526

- 527 1. While Client Authentication is important, there is a certain class of printer devices where it does not make sense.
528 Specifically, a low-end device with limited ROM space and low paper throughput may not need Client Authentication. This
529 class of device typically requires firmware designers to make trade-offs between protocols and functionality to arrive at the
530 lowest-cost solution possible. Factored into the designer's decisions is not just the size of the code, but also the testing,
531 maintenance, usefulness, and time-to-market impact for each feature delivered to the customer. Forcing such low-end
532 devices to provide security in order to claim IPP/1.1 conformance would not make business sense and could potentially stall
533 the adoption of the standard.
534
- 535 2. Print devices that have high-volume throughput and have available ROM space have a compelling argument to provide
536 support for Client Authentication that safeguards the device from unauthorized access. These devices are prone to a high
537 loss of consumables and paper if unauthorized access should occur.
538

539 8.1.2 Transport Layer Security (TLS)

540 IPP Printers SHOULD support Transport Layer Security (TLS) [RFC2246] for Server Authentication and Operation Privacy. IPP
541 Printers MAY also support TLS for Client Authentication. If an IPP Printer supports TLS, it MUST support the
542 TLS_DHE_DSS_WITH_3DES_EDE_CBC_SHA cipher suite as mandated by RFC 2246 [RFC2246]. All other cipher suites are
543 OPTIONAL. An IPP Printer MAY support Basic Authentication (described in HTTP/1.1 [RFC2617]) for Client Authentication
544 if the channel is secure. TLS with the above mandated cipher suite can provide such a secure channel.

545 If a IPP client supports TLS, it MUST support the TLS_DHE_DSS_WITH_3DES_EDE_CBC_SHA cipher suite as mandated by
546 RFC 2246 [RFC2246]. All other cipher suites are OPTIONAL.

547 The IPP Model and Semantics document defines two printer attributes ("uri-authentication-supported" and "uri-security-
548 supported") that the client can use to discover the security policy of a printer. That document also outlines IPP-specific security
549 considerations and should be the primary reference for security implications with regard to the IPP protocol itself. For backward
550 compatibility with IPP version 1.0, IPP clients and printers may also support SSL3 [ssl]. This is in addition to the security
551 required in this document.

552 8.2 Using IPP with TLS

553 IPP/1.1 uses the "Upgrading to TLS Within HTTP/1.1" mechanism [http-tls]. An initial IPP request never uses TLS. The client
554 requests a secure TLS connection by using the HTTP "Upgrade" header, while the server agrees in the HTTP response. The
555 switch to TLS occurs either because the server grants the client's request to upgrade to TLS, or a server asks to switch to TLS in
556 its response. Secure communication begins with a server's response to switch to TLS.

557 9. Interoperability with IPP/1.0 Implementations

558 It is beyond the scope of this specification to mandate conformance with previous versions. IPP/1.1 was deliberately designed,
559 however, to make supporting previous versions easy. It is worth noting that, at the time of composing this specification (1999),
560 we would expect IPP/1.1 Printer implementations to:

561 understand any valid request in the format of IPP/1.0, or 1.1;

562 respond appropriately with a response containing the same "version-number" parameter value used by the client in the
563 request.

564 And we would expect IPP/1.1 clients to:

565 understand any valid response in the format of IPP/1.0, or 1.1.

566 9.1 The "version-number" Parameter

567 The following are rules regarding the "version-number" parameter (see section 3.3):

- 568 1. Clients **MUST** send requests containing a "version-number" parameter with a '1.1' value and **SHOULD** try supplying
569 alternate version numbers if they receive a 'server-error-version-not-supported' error return in a response.
- 570 2. IPP objects **MUST** accept requests containing a "version-number" parameter with a '1.1' value (or reject the request for
571 reasons other than 'server-error-version-not-supported').
- 572 3. It is recommended that IPP objects accept any request with the major version '1' (or reject the request for reasons other
573 than 'server-error-version-not-supported'). See [ipp-mod] "versions" sub-section.
- 574 4. In any case, security **MUST NOT** be compromised when a client supplies a lower "version-number" parameter in a
575 request. For example, if an IPP/1.1 conforming Printer object accepts version '1.0' requests and is configured to enforce
576 Digest Authentication, it **MUST** do the same for a version '1.0' request.

577 9.2 Security and URL Schemes

578 The following are rules regarding security, the "version-number" parameter, and the URL scheme supplied in target attributes and
579 responses:

- 580 1. When a client supplies a request, the "printer-uri" or "job-uri" target operation attribute **MUST** have the same scheme as
581 that indicated in one of the values of the "printer-uri-supported" Printer attribute.
- 582 2. When the server returns the "job-printer-uri" or "job-uri" Job Description attributes, it **SHOULD** return the same scheme
583 ('ipp', 'https', 'http', etc.) that the client supplied in the "printer-uri" or "job-uri" target operation attributes in the Get-Job-
584 Attributes or Get-Jobs request, rather than the scheme used when the job was created. However, when a client requests
585 job attributes using the Get-Job-Attributes or Get-Jobs operations, the jobs and job attributes that the server returns
586 depends on: (1) the security in effect when the job was created, (2) the security in effect in the query request, and (3) the
587 security policy in force.
- 588 3. It is recommended that if a server registers a non-secure ipp-URL with a directory service (see [IPP-MOD] "Generic
589 Directory Schema" Appendix), then it also register an http-URL for interoperability with IPP/1.0 clients (see section 9).
- 590 4. In any case, security **MUST NOT** be compromised when a client supplies an 'http' or other non-secure URL scheme in
591 the target "printer-uri" and "job-uri" operation attributes in a request.

592 10. References

- 593 [dpa] ISO/IEC 10175 Document Printing Application (DPA), June 1996.
- 594 [http-tls] R. Khare, S. Lawrence, "Upgrading to TLS Within HTTP/1.1", <draft-ietf-tls-http-upgrade-02>, June 1999.
- 595 [iana] IANA Registry of Coded Character Sets: ftp://ftp.isi.edu/in-notes/iana/assignments/character-sets.
- 596 [ipp-iig] Hastings, Tom, et al., "Internet Printing Protocol/1.1: Implementer's Guide", draft-ietf-ipp-implementers-guide-v11-
597 00.txt, work in progress, September 27, 1999.
- 598 [ipp-mod] R. deBry, T. Hastings, R. Herriot, S. Isaacson, P. Powell, "Internet Printing Protocol/1.1: Model and Semantics",
599 <draft-ietf-ipp-model-v11-05.txt>, February 23, 2000.

- 600 [ipp-pro] Herriot, R., Butler, S., Moore, P., Turner, R., "Internet Printing Protocol/1.1: Encoding and Transport", draft-ietf-
601 ipp-protocol-v11-04-.txt, February 23, 2000.
- 602 [RFC822] Crocker, D., "Standard for the Format of ARPA Internet Text Messages", RFC 822, August 1982.
- 603 [RFC1123] Braden, S., "Requirements for Internet Hosts - Application and Support", RFC 1123, October, 1989.
- 604 [RFC1179] McLaughlin, L. III, (editor), "Line Printer Daemon Protocol" RFC 1179, August 1990.
- 605 [RFC1543] Postel, J., "Instructions to RFC Authors", RFC 1543, October 1993.
- 606 [RFC1738] Berners-Lee, T., Masinter, L., McCahill, M. , "Uniform Resource Locators (URL)", RFC 1738, December, 1994.
- 607 [RFC1759] Smith, R., Wright, F., Hastings, T., Zilles, S., and Gyllenskog, J., "Printer MIB", RFC 1759, March 1995.
- 608 [RFC1766] H. Alvestrand, " Tags for the Identification of Languages", RFC 1766, March 1995.
- 609 [RFC1808] R. Fielding, "Relative Uniform Resource Locators", RFC1808, June 1995.
- 610 [RFC1903] J. Case, et al. "Textual Conventions for Version 2 of the Simple Network Management Protocol (SNMPv2)", RFC
611 1903, January 1996.
- 612 [RFC2046] N. Freed & N. Borenstein, Multipurpose Internet Mail Extensions (MIME) Part Two: Media Types. November 1996,
613 RFC 2046.
- 614 [RFC2048] N. Freed, J. Klensin & J. Postel. Multipurpose Internet Mail Extension (MIME) Part Four: Registration Procedures.
615 November 1996 (Also BCP0013), RFC 2048.
- 616 [RFC2119] S. Bradner, "Key words for use in RFCs to Indicate Requirement Levels", RFC 2119 , March 1997.
- 617 [RFC2184] N. Freed, K. Moore, "MIME Parameter Value and Encoded Word Extensions: Character Sets, Languages, and
618 Continuations", RFC 2184, August 1997.
- 619 [RFC2234] D. Crocker et al., "Augmented BNF for Syntax Specifications: ABNF", RFC 2234. November 1997.
- 620 [RFC2246] T. Dierks et al., "The TLS Protocol", RFC 2246. January 1999.
- 621 [RFC2396] Berners-Lee, T., Fielding, R., Masinter, L., "Uniform Resource Identifiers (URI): Generic Syntax", RFC 2396,
622 August 1998.
- 623 [RFC2565] Herriot, R., Butler, S., Moore, P., Turner, R., "Internet Printing Protocol/1.0: Encoding and Transport", RFC 2565,
624 April 1999.
- 625 [RFC2566] R. deBry, T. Hastings, R. Herriot, S. Isaacson, P. Powell, "Internet Printing Protocol/1.0: Model and Semantics", rfc
626 2566, April, 1999.
- 627 [RFC2567] Wright, D., "Design Goals for an Internet Printing Protocol", RFC2567, April 1999.
- 628 [RFC2568] Zilles, S., "Rationale for the Structure and Model and Protocol for the Internet Printing Protocol", RC 2568, April
629 1999.
- 630 [RFC2569] Herriot, R., Hastings, T., Jacobs, N., Martin, J., "Mapping between LPD and IPP Protocols RFC 2569, April 1999.

- 631 [RFC2616]
632 R. Fielding, J. Gettys, J. Mogul, H. Frystyk, L. Masinter, P. Leach, T. Berners-Lee, "Hypertext Transfer Protocol -
633 HTTP/1.1", RFC 2616, June 1999.
- 634 [RFC2617]
635 J. Franks, P. Hallam-Baker, J. Hostetler, S. Lawrence, P. Leach, A. Luotonen, L. Stewart, "HTTP Authentication:
636 Basic and Digest Access Authentication", RFC 2617, June 1999.
- 637 [SSL]
638 Netscape, The SSL Protocol, Version 3, (Text version 3.02), November 1996.

639 **11. Author's Address**

640

Robert Herriot (editor)
Xerox Corporation
3400 Hillview Ave., Bldg #1
Palo Alto, CA 94304

Phone: 650-813-7696
Fax: 650-813-6860
Email: robert.herriot@pahv.xerox.com

Sylvan Butler
Hewlett-Packard
11311 Chinden Blvd.
Boise, ID 83714

Phone: 208-396-6000
Fax: 208-396-3457
Email: sbutler@boi.hp.com

Paul Moore
Peerless Systems Networking
10900 NE 8th St #900
Bellevue, WA 98004

Phone: 425-462-5852
Email: pmoore@peerless.com

Randy Turner
2Wire, Inc.
694 Tasman Dr.
Milpitas, CA 95035

Phone: 408-546-1273

John Wenn
Xerox Corporation
737 Hawaii St
El Segundo, CA 90245

IPP Mailing List: ipp@pwg.org
IPP Mailing List Subscription: ipp-request@pwg.org
IPP Web Page: <http://www.pwg.org/ipp/>

Phone: 310-333-5764
Fax: 310-333-5514
Email: jwenn@cp10.es.xerox.com

641

12. Other Participants:

Chuck Adams - Tektronix	Shivaun Albright - HP
Stefan Andersson - Axis	Jeff Barnett - IBM
Ron Bergman - Hitachi Koki Imaging Systems	Dennis Carney - IBM
Keith Carter - IBM	Angelo Caruso - Xerox
Rajesh Chawla - TR Computing Solutions	Nancy Chen - Okidata
Josh Cohen - Microsoft	Jeff Copeland - QMS
Andy Davidson - Tektronix	Roger deBry - IBM
Maulik Desai - Auco	Mabry Dozier - QMS
Lee Farrell - Canon Information Systems	Satoshi Fujitami - Ricoh
Steve Gebert - IBM	Sue Gleeson - Digital
Charles Gordon - Osicom	Brian Grimshaw - Apple
Jerry Hadsell - IBM	Richard Hart - Digital
Tom Hastings - Xerox	Henrik Holst - I-data
Stephen Holmstead	Zhi-Hong Huang - Zenographics
Scott Isaacson - Novell	Babek Jahromi - Microsoft
Swen Johnson - Xerox	David Kellerman - Northlake Software
Robert Kline - TrueSpectra	Charles Kong - Panasonic
Carl Kugler - IBM	Dave Kuntz - Hewlett-Packard
Takami Kurono - Brother	Rick Landau - Digital
Scott Lawrence - Agranot Systems	Greg LeClair - Epson
Dwight Lewis - Lexmark	Harry Lewis - IBM
Tony Liao - Vivid Image	Roy Lomicka - Digital
Pete Loya - HP	Ray Lutz - Cognisys
Mike MacKay - Novell, Inc.	David Manchala - Xerox
Carl-Uno Manros - Xerox	Jay Martin - Underscore
Stan McConnell - Xerox	Larry Masinter - Xerox
Sandra Matts - Hewlett Packard	Peter Michalek - Shinesoft
Ira McDonald - High North Inc.	Mike Moldovan - G3 Nova
Tetsuya Morita - Ricoh	Yuichi Niwa - Ricoh
Pat Nogay - IBM	Ron Norton - Printronics
Hugo Parra, Novell	Bob Pentecost - Hewlett-Packard
Patrick Powell - Astart Technologies	Jeff Rackowitz - Intermec
Eric Random - Peerless	Rob Rhoads - Intel
Xavier Riley - Xerox	Gary Roberts - Ricoh
David Roach - Unisys	Stuart Rowley - Kyocera
Yuji Sasaki - Japan Computer Industry	Richard Schneider - Epson
Kris Schoff - HP	Katsuaki Sekiguchi - Canon Information Systems
Bob Setterbo - Adobe	Gail Songer - Peerless
Hideki Tanaka - Cannon Information Systems	Devon Taylor - Novell, Inc.
Mike Timperman - Lexmark	Atsushi Uchino - Epson
Shigeru Ueda - Canon	Bob Von Andel - Allegro Software

Steve Zilles - Adobe	Rob Zirnstein - Canon Information Systems
----------------------	---

643
644

645 **13. Appendix A: Protocol Examples**

646 **13.1 Print-Job Request**

647 The following is an example of a Print-Job request with job-name, copies, and sides specified. The "ipp-attribute-fidelity"
648 attribute is set to 'true' so that the print request will fail if the "copies" or the "sides" attribute are not supported or their values are
649 not supported.

Octets	Symbolic Value	Protocol field
0x0101	1.1	version-number
0x0002	Print-Job	operation-id
0x00000001	1	request-id
0x01	start operation-attributes	operation-attributes-tag
0x47	charset type	value-tag
0x0012		name-length
attributes-charset	attributes-charset	name
0x0008		value-length
us-ascii	US-ASCII	value
0x48	natural-language type	value-tag
0x001B		name-length
attributes-natural-language	attributes-natural-language	name
0x0005		value-length
en-us	en-US	value
0x45	uri type	value-tag
0x000B		name-length
printer-uri	printer-uri	name
0x0015		value-length
ipp://forest/pinetree	printer pinetree	value
0x42	nameWithoutLanguage type	value-tag
0x0008		name-length
job-name	job-name	name
0x0006		value-length
foobar	foobar	value
0x22	boolean type	value-tag
0x0016		name-length
ipp-attribute-fidelity	ipp-attribute-fidelity	name
0x0001		value-length
0x01	true	value
0x02	start job-attributes	job-attributes-tag
0x21	integer type	value-tag
0x0006		name-length
copies	copies	name
0x0004		value-length
0x00000014	20	value
0x44	keyword type	value-tag
0x0005		name-length
sides	sides	name
0x0013		value-length
two-sided-long-edge	two-sided-long-edge	value
0x03	end-of-attributes	end-of-attributes-tag
%!PS...	<PostScript>	data

650 13.2 Print-Job Response (successful)

651 Here is an example of a successful Print-Job response to the previous Print-Job request. The printer supported the "copies" and
652 "sides" attributes and their supplied values. The status code returned is 'successful-ok'.

Octets	Symbolic Value	Protocol field
0x0101	1.1	version-number
0x0000	successful-ok	status-code
0x00000001	1	request-id
0x01	start operation-attributes	operation-attributes-tag
0x47	charset type	value-tag
0x0012		name-length
attributes-charset	attributes-charset	name
0x0008		value-length
us-ascii	US-ASCII	value
0x48	natural-language type	value-tag
0x001B		name-length
attributes-natural-language	attributes-natural-language	name
0x0005		value-length
en-us	en-US	value
0x41	textWithoutLanguage type	value-tag
0x000E		name-length
status-message	status-message	name
0x000D		value-length
successful-ok	successful-ok	value
0x02	start job-attributes	job-attributes-tag
0x21	integer	value-tag
0x0006		name-length
job-id	job-id	name
0x0004		value-length
147	147	value
0x45	uri type	value-tag
0x0007		name-length
job-uri	job-uri	name
0x0019		value-length
ipp://forest/pinetree/123	job 123 on pinetree	value
0x23	enum type	value-tag
0x0009		name-length
job-state	job-state	name
0x0004		value-length
0x0003	pending	value
0x03	end-of-attributes	end-of-attributes-tag

653 13.3 Print-Job Response (failure)

654 Here is an example of an unsuccessful Print-Job response to the previous Print-Job request. It fails because, in this case, the
655 printer does not support the "sides" attribute and because the value '20' for the "copies" attribute is not supported. Therefore, no
656 job is created, and neither a "job-id" nor a "job-uri" operation attribute is returned. The error code returned is 'client-error-
657 attributes-or-values-not-supported' (0x040B).
658

Octets	Symbolic Value	Protocol field
0x0101	1.1	version-number
0x040B	client-error-attributes-or-values-not-supported	status-code
0x00000001	1	request-id
0x01	start operation-attributes	operation-attribute tag
0x47	charset type	value-tag
0x0012		name-length
attributes-charset	attributes-charset	name
0x0008		value-length
us-ascii	US-ASCII	value
0x48	natural-language type	value-tag
0x001B		name-length
attributes-natural-language	attributes-natural-language	name
0x0005		value-length
en-us	en-US	value
0x41	textWithoutLanguage type	value-tag
0x000E		name-length
status-message	status-message	name
0x002F		value-length
client-error-attributes-or-values-not-supported	client-error-attributes-or-values-not-supported	value
0x05	start unsupported-attributes	unsupported-attributes tag
0x21	integer type	value-tag
0x0006		name-length
copies	copies	name
0x0004		value-length
0x00000014	20	value
0x10	unsupported (type)	value-tag
0x0005		name-length
sides	sides	name
0x0000		value-length
0x03	end-of-attributes	end-of-attributes-tag

659 **13.4 Print-Job Response (success with attributes ignored)**

660 Here is an example of a successful Print-Job response to a Print-Job request like the previous Print-Job request, except that the
661 value of 'ipp-attribute-fidelity' is false. The print request succeeds, even though, in this case, the printer supports neither the
662 "sides" attribute nor the value '20' for the "copies" attribute. Therefore, a job is created, and both a "job-id" and a "job-uri"
663 operation attribute are returned. The unsupported attributes are also returned in an Unsupported Attributes Group. The error code
664 returned is 'successful-ok-ignored-or-substituted-attributes' (0x0001).
665

Octets	Symbolic Value	Protocol field
0x0101	1.1	version-number
0x0001	successful-ok-ignored-or-substituted-attributes	status-code
0x00000001	1	request-id
0x01	start operation-attributes	operation-attributes-tag
0x47	charset type	value-tag
0x0012		name-length
attributes-charset	attributes-charset	name
0x0008		value-length
us-ascii	US-ASCII	value
0x48	natural-language type	value-tag
0x001B		name-length
attributes-natural-language	attributes-natural-language	name
0x0005		value-length
en-us	en-US	value
0x41	textWithoutLanguage type	value-tag
0x000E		name-length
status-message	status-message	name
0x002F		value-length
successful-ok-ignored-or-substituted-attributes	successful-ok-ignored-or-substituted-attributes	value
0x05	start unsupported-attributes	unsupported-attributes tag
0x21	integer type	value-tag
0x0006		name-length
copies	copies	name
0x0004		value-length
0x00000014	20	value
0x10	unsupported (type)	value-tag
0x0005		name-length
sides	sides	name
0x0000		value-length
0x02	start job-attributes	job-attributes-tag
0x21	integer	value-tag
0x0006		name-length
job-id	job-id	name
0x0004		value-length
147	147	value
0x45	uri type	value-tag
0x0007		name-length
job-uri	job-uri	name
0x0019		value-length
ipp://forest/pinetree/123	job 123 on pinetree	value
0x23	enum type	value-tag
0x0009		name-length
job-state	job-state	name
0x0004		value-length
0x0003	pending	value
0x03	end-of-attributes	end-of-attributes-tag

667 **13.5 Print-URI Request**

668 The following is an example of Print-URI request with copies and job-name parameters:

Octets	Symbolic Value	Protocol field
0x0101	1.1	version-number
0x0003	Print-URI	operation-id
0x00000001	1	request-id
0x01	start operation-attributes	operation-attributes-tag
0x47	charset type	value-tag
0x0012		name-length
attributes-charset	attributes-charset	name
0x0008		value-length
us-ascii	US-ASCII	value
0x48	natural-language type	value-tag
0x001B		name-length
attributes-natural-language	attributes-natural-language	name
0x0005		value-length
en-us	en-US	value
0x45	uri type	value-tag
0x000B		name-length
printer-uri	printer-uri	name
0x0015		value-length
ipp://forest/pinetree	printer pinetree	value
0x45	uri type	value-tag
0x000C		name-length
document-uri	document-uri	name
0x0011		value-length
ftp://foo.com/foo	ftp://foo.com/foo	value
0x42	nameWithoutLanguage type	value-tag
0x0008		name-length
job-name	job-name	name
0x0006		value-length
foobar	foobar	value
0x02	start job-attributes	job-attributes-tag
0x21	integer type	value-tag
0x0006		name-length
copies	copies	name
0x0004		value-length
0x00000001	1	value
0x03	end-of-attributes	end-of-attributes-tag

669 **13.6 Create-Job Request**

670 The following is an example of Create-Job request with no parameters and no attributes:

Octets	Symbolic Value	Protocol field
0x0101	1.1	version-number
0x0005	Create-Job	operation-id
0x00000001	1	request-id
0x01	start operation-attributes	operation-attributes-tag
0x47	charset type	value-tag
0x0012		name-length
attributes-charset	attributes-charset	name
0x0008		value-length
us-ascii	US-ASCII	value
0x48	natural-language type	value-tag
0x001B		name-length
attributes-natural-language	attributes-natural-language	name
0x0005		value-length
en-us	en-US	value
0x45	uri type	value-tag
0x000B		name-length
printer-uri	printer-uri	name
0x0015		value-length
ipp://forest/pinetree	printer pinetree	value
0x03	end-of-attributes	end-of-attributes-tag

671 **13.7 Get-Jobs Request**

672 The following is an example of Get-Jobs request with parameters but no attributes:

Octets	Symbolic Value	Protocol field
0x0101	1.1	version-number
0x000A	Get-Jobs	operation-id
0x00000123	0x123	request-id
0x01	start operation-attributes	operation-attributes-tag
0x47	charset type	value-tag
0x0012		name-length
attributes-charset	attributes-charset	name
0x0008		value-length
us-ascii	US-ASCII	value
0x48	natural-language type	value-tag
0x001B		name-length
attributes-natural-language	attributes-natural-language	name
0x0005		value-length
en-us	en-US	value
0x45	uri type	value-tag
0x000B		name-length
printer-uri	printer-uri	name
0x0015		value-length
ipp://forest/pinetree	printer pinetree	value
0x21	integer type	value-tag
0x0005		name-length
limit	limit	name
0x0004		value-length
0x00000032	50	value
0x44	keyword type	value-tag
0x0014		name-length
requested-attributes	requested-attributes	name
0x0006		value-length
job-id	job-id	value
0x44	keyword type	value-tag
0x0000	additional value	name-length
0x0008		value-length
job-name	job-name	value
0x44	keyword type	value-tag
0x0000	additional value	name-length
0x000F		value-length
document-format	document-format	value
0x03	end-of-attributes	end-of-attributes-tag

673 13.8 Get-Jobs Response

674 The following is an of Get-Jobs response from previous request with 3 jobs. The Printer returns no information about the second
675 job (because of security reasons):

Octets	Symbolic Value	Protocol field
0x0101	1.1	version-number
0x0000	successful-ok	status-code
0x00000123	0x123	request-id (echoed back)
0x01	start operation-attributes	operation-attribute-tag
0x47	charset type	value-tag
0x0012		name-length
attributes-charset	attributes-charset	name
0x000A		value-length
ISO-8859-1	ISO-8859-1	value
0x48	natural-language type	value-tag
0x001B		name-length
attributes-natural-language	attributes-natural-language	name
0x0005		value-length
en-us	en-US	value
0x41	textWithoutLanguage type	value-tag
0x000E		name-length
status-message	status-message	name
0x000D		value-length
successful-ok	successful-ok	value
0x02	start job-attributes (1st object)	job-attributes-tag
0x21	integer type	value-tag
0x0006		name-length
job-id	job-id	name
0x0004		value-length
147	147	value
0x36	nameWithLanguage	value-tag
0x0008		name-length
job-name	job-name	name
0x000C		value-length
0x0005		sub-value-length
fr-ca	fr-CA	value
0x0003		sub-value-length
fou	fou	name
0x02	start job-attributes (2nd object)	job-attributes-tag
0x02	start job-attributes (3rd object)	job-attributes-tag
0x21	integer type	value-tag
0x0006		name-length
job-id	job-id	name
0x0004		value-length
148	149	value
0x36	nameWithLanguage	value-tag
0x0008		name-length
job-name	job-name	name
0x0012		value-length
0x0005		sub-value-length
de-CH	de-CH	value
0x0009		sub-value-length
isch guet	isch guet	name
0x03	end-of-attributes	end-of-attributes-tag

676 **14. Appendix B: Registration of MIME Media Type Information for** 677 **"application/ipp"**

678 This appendix contains the information that IANA requires for registering a MIME media type. The information following this
679 paragraph will be forwarded to IANA to register application/ipp whose contents are defined in Section 3 "Encoding of the
680 Operation Layer" in this document:

681 **MIME type name:** application

682 **MIME subtype name:** ipp

683 A Content-Type of "application/ipp" indicates an Internet Printing Protocol message body (request or response). Currently there
684 is one version: IPP/1.1, whose syntax is described in Section 3 "Encoding of the Operation Layer" of [ipp-pro], and whose
685 semantics are described in [ipp-mod].

686 **Required parameters:** none

687 **Optional parameters:** none

688 **Encoding considerations:**

689 IPP/1.1 protocol requests/responses MAY contain long lines and ALWAYS contain binary data (for example attribute value
690 lengths).

691 **Security considerations:**

692 IPP/1.1 protocol requests/responses do not introduce any security risks not already inherent in the underlying transport protocols.
693 Protocol mixed-version interworking rules in [ipp-mod] as well as protocol encoding rules in [ipp-pro] are complete and
694 unambiguous.

695 **Interoperability considerations:**

696 IPP/1.1 requests (generated by clients) and responses (generated by servers) MUST comply with all conformance requirements
697 imposed by the normative specifications [ipp-mod] and [ipp-pro]. Protocol encoding rules specified in [ipp-pro] are
698 comprehensive, so that interoperability between conforming implementations is guaranteed (although support for specific
699 optional features is not ensured). Both the "charset" and "natural-language" of all IPP/1.1 attribute values which are a
700 LOCALIZED-STRING are explicit within IPP protocol requests/responses (without recourse to any external information in
701 HTTP, SMTP, or other message transport headers).

702 **Published specifications:**

703 [ipp-mod] Isaacson, S., deBry, R., Hastings, T., Herriot, R., Powell, P., "Internet Printing Protocol/1.1: Model and Semantics"
704 draft-ietf-ipp-model-v11-05.txt, February 23, 2000.

705 [ipp-pro] Herriot, R., Butler, S., Moore, P., Turner, R., "Internet Printing Protocol/1.1: Encoding and Transport", draft-ietf-
706 ipp-protocol-v11-04.txt, February 23, 2000.

707 **Applications which use this media type:**

708 Internet Printing Protocol (IPP) print clients and print servers, communicating using HTTP/1.1 (see [IPP-PRO]), SMTP/ESMTP,
709 FTP, or other transport protocol. Messages of type "application/ipp" are self-contained and transport-independent, including
710 "charset" and "natural-language" context for any LOCALIZED-STRING value.

711 **Person & email address to contact for further information:**

712 Tom Hastings
713 Xerox Corporation
714 737 Hawaii St. ESAE-231
715 El Segundo, CA

716 Phone: 310-333-6413
717 Fax: 310-333-5514
718 Email: hastings@cp10.es.xerox.com

719 or

720 Robert Herriot
721 Xerox Corporation
722 3400 Hillview Ave., Bldg #1
723 Palo Alto, CA 94304

724 Phone: 650-813-7696
725 Fax: 650-813-6860
726 Email: robert.herriot@pahv.xerox.com

727 **Intended usage:**

728 COMMON

729 **15. Appendix C: Changes from IPP/1.0**

730 IPP/1.1 is identical to IPP/1.0 [RFC2565] with the follow changes:

731 1. Attributes values that identify a printer or job object use a new 'ipp' scheme. The 'http' and 'https' schemes are supported only

743

16. Full Copyright Statement

744
745
746
747
748
749
750

The IETF takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on the IETF's procedures with respect to rights in standards-track and standards-related documentation can be found in BCP-11[BCP-11]. Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF Secretariat.

751
752
753

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights which may cover technology that may be required to practice this standard. Please address the information to the IETF Executive Director.

754

Copyright (C)The Internet Society (1999). All Rights Reserved

755
756
757
758

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which